



Epoxy Coated - Smooth Dowels

Description:

OCM, Inc's Epoxy Coated - Smooth Dowels allow for contraction and expansion of concrete due to moisture changes, while keeping the concrete from lifting. The epoxy coating helps to better protect the dowels from weather and moisture changes.

Features:

- Long-lasting protective epoxy coating.
- Prevents concrete lifting.
- Made from high-strength steel. Meets ASTM A615 Grade 60.
- Available in varying lengths.
- Meets the following specifications: ASTM A775, ASTM A1078, ASTM A884, AASHTO M284, AASHTO M254.

Additional Notes: Additional lengths available upon request. Water seal available upon request. SWL provides a safety factor of approximately 2 to 1.

Item Number	Weight Per Piece (lbs)	Description	Pallet Quantity
SD50X12E	0.67	SMOOTH DOWEL - 1/2" X 12" - EPOXY COATED	2200
SD50X18E	1	SMOOTH DOWEL - 1/2" X 18" - EPOXY COATED	1500
SD50X24E	1.34	SMOOTH DOWEL - 1/2" X 24" - EPOXY COATED	1100
SD625X18E	1.56	SMOOTH DOWEL - 5/8" X 18" - EPOXY COATED	1000
SD625X24E	2.09	SMOOTH DOWEL - 5/8" X 24" - EPOXY COATED	800
SD75X18E	2.25	SMOOTH DOWEL - 3/4" X 18" - EPOXY COATED	1000
SD75X24E	3.02	SMOOTH DOWEL - 3/4" X 24" - EPOXY COATED	700
SD100X18E	4.01	SMOOTH DOWEL - 1" X 18" - EPOXY COATED	600
SD100X24E	5.34	SMOOTH DOWEL - 1" X 24" - EPOXY COATED	450
SD125X18E	6.26	SMOOTH DOWEL - 1 1/4" X 18" - EPOXY COATED	380
SD125X24E	8.34	SMOOTH DOWEL - 1 1/4" X 24" - EPOXY COATED	290
SD150X18E	9.02	SMOOTH DOWEL - 1-1/2" X 18" - EPOXY COATED	270
SD150X24E	12.02	SMOOTH DOWEL - 1-1/2" X 24" - EPOXY COATED	200