

## 2 Strut Conefast Coil Tie 1/2"

### Description:

OCM Conefast Coil Ties are one of the most economical and versatile form tie systems available. They are commonly used with self cleaning Coil Rod or Coil Bolts. The Conefast coil Ties have extended coils that protrude beyond the end of the struts allowing for a Conefast (Screw On) Cone to be attached.



### Features:

- When used with cones they will provide a setback of metal to reduce corrosion staining on finished wall
- Can be provided as plain or mechanically galvanized
- When used with cones can be used as combination tie and form spreader
- Used for architectural walls, and can also be used without cones

**Additional Notes:** Additional lengths available upon request. Water seal available upon request. SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	Tie Length (in)	Wall Thickness (With 1" Setback) (in)	Weight Per Piece (lbs)	Box Quantity
CT5042SP	4,500 lbs.	42	44	1.1	100
CT5036SP	4,500 lbs.	36	38	1	100
CT5034SP	4,500 lbs.	34	36	0.926	100
CT5032SP	4,500 lbs.	32	34	0.88	100
CT5022SP	4,500 lbs.	22	24	0.65	100
CT5030SP	4,500 lbs.	30	32	0.834	100
CT5028SP	4,500 lbs.	28	30	0.788	100
CT5026SP	4,500 lbs.	26	28	0.742	100
CT5024SP	4,500 lbs.	24	26	0.696	100
CT5004SP	4,500 lbs.	4	6	0.32	100
CT5020SP	4,500 lbs.	20	22	0.604	100

Item Number	Safe Working Load (lbs)	Tie Length (in)	Wall Thickness (With 1" Setback) (in)	Weight Per Piece (lbs)	Box Quantity
CT5018SP	4,500 lbs.	18	20	0.558	100
CT5016SP	4,500 lbs.	16	18	0.512	100
CT5014SP	4,500 lbs.	14	16	0.466	100
CT5012SP	4,500 lbs.	12	14	0.42	100
CT5010SP	4,500 lbs.	10	12	0.36	100
CT5008SP	4,500 lbs.	8	10	0.32	100
CT5006SP	4,500 lbs.	6	8	0.32	100