

## Coil Bolts

### Description:

OCM Coil Bolts are made from high strength steel, and are used with different types of coil thread nuts and inserts in concrete formwork, bridge deck forming, or precast concrete applications.



### Features:

- Standard sizes of 1/2" and 3/4" Diameter up to 6" length are readily available
- Coil Thread is self cleaning and ideal for dirty job sites or use in concrete formwork
- Special sizes and lengths can be fabricated upon request

**Additional Notes:** SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	D Size (in)	AC Across Flats (in)	L Length (in)	Weight Per 100 Pieces (lbs)	Carton Quantity
62S400CBH0P	7,500	5/8"	1"	4"	35.4	100
62S200CBH0P	7,500	5/8"	1"	2"	21.8	100
75S600CBH0P	9,000	3/4"	1-1/8"	6"	72.4	75
75S500CBH0P	9,000	3/4"	1-1/8"	5"	62.5	75
75S400CBH0P	9,000	3/4"	1-1/8"	4"	52.5	100
75S350CBH0P	9,000	3/4"	1-1/8"	3-1/2"	47.8	100
75S200CBH0P	9,000	3/4"	1-1/8"	2"	32.8	150
75S300CBH0P	9,000	3/4"	1-1/8"	3"	42.7	100
75S250CBH0P	9,000	3/4"	1-1/8"	2-1/2"	39.4	150
50A150CBH0P	4,125	1/2"	3/4"	1-1/2"	10.6	500
50A600CBH0P	4,125	1/2"	3/4"	6"	30.7	150
50A500CBH0P	4,125	1/2"	3/4"	5"	26.3	200
50A400CBH0P	4,125	1/2"	3/4"	4"	21.6	250
50A350CBH0P	4,125	1/2"	3/4"	3-1/2"	19.4	250

ItemNumber	Safe Working Load (lbs)	D Size (in)	AC Across Flats (in)	L Length (in)	Weight Per 100 Pieces (lbs)	Carton Quantity
50A300CBH0P	4,125	1/2"	3/4"	3"	17.1	300
50A250CBH0P	4,125	1/2"	3/4"	2-1/2"	15.1	400
50A200CBH0P	4,125	1/2"	3/4"	2"	12.8	500