



Coil Rod

Description:

OCM Coil Rod is manufactured with continuous thread from high strength cold rolled steel. Coil Tie Bar is self cleaning and ideal for dirty job sites or for use in concrete formwork and shuttering applications.

Features:

- Available in several diameters up to 1 1/2"
- Comes in 12ft lengths, but coupler are available for longer lengths
- Can be easily field cut with a carborundum blade or bolt cutters
- Requires 2 Standard Coil Nuts or 1 Tall Coil Nut to develop Ultimate Load
- 1/2" diameter is made from C1035, C1038, or C1045 steel
- 5/8" and 3/4" diameter is made from C1035 or C1045 steel
- 7/8", 1", 1-1/4", and 1-1/2" are made from C1045 steel

Additional Notes: SWL provides a safety factor of approximately 2 to 1. Special order cut lengths are available by request.

Item Number	Safe Working Load (lbs)	D Size (in)	L Length (ft)	Weight Per Piece (lbs)
50ACTRP144-G	9,000	1/2"	12FT	6.4
75ACTRP144-G	18,000	3/4"	12FT	13.4
62ACTRP144	12,000	5/8"	12FT	8.5
50ACTRP144	9,000	1/2"	12FT	6.4
75ACTRP144	18,000	3/4"	12FT	13.4
87ACTRP144	31,000	7/8"	12FT	20.04
100ACTRP144	38,000	1"	12FT	24.48
125ACTRP144	56,000	1-1/4"	12FT	41.76
150ACTRP144	68,000	1-1/2"	12FT	72.12
50ACTRP72	9,000	1/2"	6FT	53
75ACTRP72	18,000	3/4"	6FT	118
100ACTRP72	38,000	1"	6FT	118
125ACTRP72	56,000	1-1/4"	6FT	340