


## **Combo Ties**



## **Description:**

OCM Combo Ties are manufactured with either a Standard Loop Tie or Snap Tie on one end and a 1/2" Coil Tie on the other end. They can be used in Steel Frame Form or Snap Tie one sided or blind side forming applications.

## **Features:**

- Standard sizes of 4", 6", and 8" are in stock, but can be used with field cut lengths of Coil Rod to form different size walls
- They provide good Safe Working Loads
- Special sizes and lengths can be fabricated upon request

**Additional Notes:** 1/2" Heavy Duty (6,750 SWL) available upon request - 4 Strut Available. Additional lengths available upon request. Waterseal available upon request. SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	Wall Size (in)	Weight Per Piece (lbs)	Carton Quantity	Description
COMBO- 50C/HDL-4	3,000	4	0.25	100	HD Loop Tie and 1/2" Coil Tie
COMBO- 50C/HDL-6	3,000	6	0.27	100	HD Loop Tie and 1/2" Coil Tie
COMBO- 50C/HDL-8	3,000	8	0.29	100	HD Loop Tie and 1/2" Coil Tie
COMBO- 50C/LEST	2,250	6	0.3	100	Snap Tie and 1/2" Coil Tie
COMBO- 50C/AFT	3,000	6	0.35	100	Aluminum and Coil Tie
COMBO- 50C/RT-6	2.25	6	0.35	100	Resi and Coil Tie