



She Bolts

Description:

OCM Inc. She-Bolts are heavy duty, reusable form ties for medium and heavy concrete construction. They are used with Inside Rods or Coil Rod that can be cut in the field to any desired length based on form thickness that is required. She-Bolts are meant to be reused, but they do wear so they must be continually inspected. When wear or damage is noted, they must be replaced. A water-proof grease should be applied to the embedded portion of the she-bolt to facilitate removal.

Features:

- Reusable form ties (inside rod needs replacing each time).

Additional Notes: SWL provides a safety factor of approximately 2 to 1.

Item Number	Safe Working Load (lbs)	Length (in)	Ext. Thread Dia. (in)	She Bolt External Thread Type	Inside Tie Rod Thread Dia. (in)	Inside Tie Rod Thread Type
SB7550-17ACME	9,000	17"	3/4"	Acme	1/2"	NC
SBA7550-20P	9,000	20"	3/4"	Acme	1/2"	Coil
SB7550-17P	9,000	17"	3/4"	Coil	1/2"	Coil
SB7550-24P	9,000	24"	3/4"	Coil	1/2"	Coil
SB7550-20P	9,000	20"	3/4"	Coil	1/2"	Coil
SB12575-18P	18,000	18"	1-1/4"	Coil	3/4"	Coil
SB12575-20	18,000	20"	1-1/4"	Coil	3/4"	Coil
SB12575-24P	18,000	24"	1-1/4"	Coil	3/4"	Coil
SB12575-30	18,000	30"	1-1/4"	Coil	3/4"	Coil
SB150100-20P	37,500	20"	1-1/2"	Coil	1"	Coil
SB150100-24P	37,500	24"	1-1/2"	Coil	1"	Coil
SB150100-30P	37,500	30"	1-1/2"	Coil	1"	Coil