



Slab Bolster Epoxy

Description:

OCM Slab Bolster Epoxy Coated metal bar supports are used in commercial concrete projects to support upper and lower mats of reinforcing steel in elevated concrete decks, footings, slab on grade, slab on metal deck, bridge decks and other applications.

Features:

- Available in heights ranging from 3/4" to 3" in 1/4" increments. Other sizes available upon request.
- Manufactured in 60" Lengths.
- Epoxy Coating is done at approved coating suppliers within the United States with epoxypowder that is supplied by manufacturers that supply 100% Made in USA material. The epoxy powder meets the requirements of ASTM A775, AASHTOM254 and /or ASHTOM284 and is applied at a minimum thickness of 6 mils to satisfy the DOT requirements for all states.
- The Bar Supports supplied by OCM Inc. meet CRSI and "Buy America" requirements.

Additional Notes: Please inquire about domestic and CRSI requirements.

Item Number	Weight Per Piece (lbs)	Height (in)	Bundle Quantity (lf)
SB75-E	0.21	3/4"	100
SB100-E	0.22	1"	100
SB125-E	0.23	1-1/4"	100
SB150-E	0.23	1-1/2"	100
SB200-E	0.23	2"	100
SB225-E	0.24	2-1/4"	100
SB250-E	0.25	2-1/2"	100
SB300-E	0.27	3"	100