


Anchor Bolts

Description:

OCM Inc Plain or Hot Dipped galvanized anchor bolts are engineered for professional use in commercial, industry and residential applications. Galvanized anchor bolts provide long term protection ensuring durability and long service life. These anchor bolts are manufactured for use in moist environments where more rust resistance is required. Galvanized material coats steel with a thick material that provides high resistance against corrosion and rust. Typical applications include base plate anchorage and sill plate anchorage to freshly poured concrete.



Features:

- Galvanized anchor bolts provide long term protection ensuring durability and long service life.
- OCM Anchor Bolts have been approved for exterior use with all types of treated lumber.
- OCM Anchor Bolts provide excellent holding power and stability.
- OCM Anchor Bolts comply with industry standards: ASTM - A307 and ASTM A153. Class C.

Additional Notes: Please inquire about domestic and CRSI requirements.

Item Number	D Size (in)	L Length (in)	Weight Per Piece (lbs)	Plating
AB6208P	5/8"	8"	0.72	Plain
AB7524HDG	3/4"	24"	2.84	Hot Dip Galv.
AB7516HDG	3/4"	16"	2.4	Hot Dip Galv.
AB7512HDG	3/4"	12"	1.62	Hot Dip Galv.
AB7518P	3/4"	18"	1.2	Plain
AB6218HDG	5/8"	18"	1.42	Hot Dip Galv.
AB6212HDG	5/8"	12"	1.22	Hot Dip Galv.
AB6210HDG	5/8"	10"	0.86	Hot Dip Galv.
AB6208HDG	5/8"	8"	0.74	Hot Dip Galv.

Item Number	D Size (in)	L Length (in)	Weight Per Piece (lbs)	Plating
AB6212P	5/8"	12"	1.2	Plain
AB6210P	5/8"	10"	0.84	Plain
AB5018HDG	1/2"	18"	0.86	Hot Dip Galv.
AB5016HDG	1/2"	16"	0.74	Hot Dip Galv.
AB5014HDG	1/2"	14"	0.68	Hot Dip Galv.
AB508P	1/2"	8"	0.46	Plain
AB5012HDG	1/2"	12"	0.63	Hot Dip Galv.
AB5010HDG	1/2"	10"	0.54	Hot Dip Galv.
AB508HDG	1/2"	8"	0.46	Hot Dip Galv.
AB506HDG	1/2"	6"	0.38	Hot Dip Galv.
AB5012P	1/2"	12"	0.63	Plain
AB5010P	1/2"	10"	0.54	Plain