



Speed Lock Ties

Description:

OCM SPEED LOCK TIES are used to build wood forming using standard $\frac{3}{4}$ " plyform with 2x4's for the walers and stiff backs (strong backs).

Features:

- The ties feature a self-centering cone that will adapt to imperfect alignment and dimensional variances in the lumber without affecting the break back operation.
- Available in standard sizes and made to order special sizes.
- 2250# safe working load (2:1 safety factor) adjust tie pattern/pour rate according to specific job requirements.
- 13/16th Hole required.
- Uses less lumber and requires less nailing than other typical wood-based hand-set systems.
- Adaptable to most other types of wall forming systems.
- Great for radius forming.

Additional Notes: SWL provides a safety factor of approximately 2 to 1. Special lengths and Stainless Steel also available.

Item Number	Safe Working Load (lbs)	Wall Size (in)	Weight Per Piece (lbs)
SLT-42B	2,250	42	0.62
SLT-26B	2,250	26	0.44
SLT-27B	2,250	27	0.45
SLT-28B	2,250	28	0.46
SLT-29B	2,250	29"	0.47
SLT-30B	2,250	30	0.48
SLT-36B	2,250	36	0.53
SLT-38B	2,250	38"	0.54
SLT-40B	2,250	40	0.55
SLT-25B	2,250	25"	0.43
SLT-44B	2,250	44"	0.64
SLT-48B	2,250	48	0.72
SLT-51B	2,250	51"	0.73
SLT-54B	2,250	54	0.75
SLT-57B	2,250	57"	0.77

Item Number	Safe Working Load (lbs)	Wall Size (in)	Weight Per Piece (lbs)
SLT-59B	2,250	59"	0.79
SLT-60B	2,250	60	0.8
SLT-24B	2,250	24	0.44
SLT-06B	2,250	6	0.21
SLT-22B	2,250	22"	0.41
SLT-21B	2,250	21"	0.39
SLT-20B	2,250	20	0.38
SLT-18B	2,250	18	0.36
SLT-16B	2,250	16	0.34
SLT-15B	2,250	15	0.33
SLT-14B	2,250	14	0.31
SLT-13B	2,250	13"	0.29
SLT-12B	2,250	12	0.28
SLT-11B	2,250	11	0.26
SLT-10B	2,250	10	0.25
SLT-09B	2,250	9	0.24
SLT-08B	2,250	8	0.23
SLT-07B	2,250	7	0.22