

OCMQS275



A quality, chemically-neutral, petroleum based form release agent. OCM Quick Strip reacts with the alkali in the concrete to form a soap film that inhibits the bonding of fresh concrete to the formwork. Forms are ready for re use almost instantly. OCM Quick Strip produces a smooth, void free, architectural concrete surface. VOC compliant.

General Uses

OCM Quick Strip will aid in the release of the form from hardened concrete on the widest range of forming materials.

Part Number	OCMQS275
Packaging	275 GAL TOTE
Standards	This product meets the requirements of Corps of Engineers specifications CW 03101, section 2.1.2
Instructions For Use	OCM Quick Strip should be applied in a thin uniform film with a sprayer, brush or roller. No special application equipment is necessary, but a spray application is the most practical. Ponding or pudd
Specific Applications	Aluminum, High Density Plywood, Plastic, Steel: 1750 sq. ft. per U.S. gallon, BB Grade Plyform: 1000 sq. ft. per U.S. gallon, Medium Density Plywood: 1500 sq. ft. per U.S. gallon, Plywood & other dimensional lumber: 750 sq. ft. per U.S. gallon

Limitations/Warning	Colder temperatures will increase the viscosity of OCM Quick Strip., Contains petroleum distillates. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, call physician. If splashed in eyes, wash repeatedly with clean water a, Do not over apply., Do not use as a bond breaker for tilt-up construction., Do not use on plaster molds unless coated with a suitable sealer., Do not use on Styrofoam or latex molds., Refer to Safety Data Sheet before use.
Technical Services	OCM Inc. Technical Service Department provides complete product and technical support.